ACCESSORIES

Headlamp Controller Power Supply Unit Modifier Single Yoke, Double Yoke Link 2, Link 4 DC Cable, AC Cable Battery Mount VL or AB

LIGHT ENGINE

LEDs:

Bag

Red, Lime, Green, Blue, Amber, White

NUMBER of LEDs: 1080

LIGHT APERTURE

1m at 5600K: 7550 Lux

1m at 3200K: 7377 Lux

POWER

Battery Powered: External V-Mount Battery Voltage Range: 24 - 35 V <u>Power Consumption:</u>

380 W max.

DIMMING

Smooth, 100 – 0%, Linear / Square / S Curve

MODIFIER

Frosted Acrylic Diffuser: Flat, Dome

Snapbag Single+Double Snapgrid Single+Double Dome Silk Double


SIZE/WEIGHT

120 x 36 x 8,5 cm 8 kg

WATERPROOF RATING

IP20

DMG LUMIÉRE MAXI MIX



SPECIALS

Gel Mode Effect Mode Source Matching Mode Connecting of multiple lights for vaiable light sizes Micro Shadows without Diffusor

LIGHT/COLOR SPECS

MODES:

White/ Gel / Color

WHITE LIGHT:

1700K - 10.000K

COLOR RENDITION: CRI Average: >95 TLCI Average: >90

MOUNT

Yoke with 16mm female /28mm male hybrid spigot Imperial: baby pin receiver, junior pin male

CONTROL OPTIONS

Controller with Rubber Keypad DMX 512 Wired Wireless DMX Bluetooth with myMIX Mobile App LAN (Art-Net) WiFi

CONNECTIVITY

XLR5 female XLR5 male RJ45 Chogori 2 pin VDC input Micro USB CNLINKO LP-20 7 pin output

