

ACCESSORIES

Headlamp
powerCon Cable
Omega Adaptor
Power cord including powerCON connector
Gel frame adaptor
Safety

MODIFIER

EXTERNAL:
None

INTERNAL:
Gobos
Frost
Iris
Zoom
Focus

SIZE/WEIGHT

80,5 x 48,3 x 33,5 cm
36,9 kg

WATERPROOF RATING

IP20

LIGHT/COLOR SPECS

COLOR MODES:
Colour mixing: CMY/RGB OR RGBAL
8 Bit or 16 Bit

WHITE LIGHT:
Variable CCT 2.700K - 8.000K

COLOR RENDITION:
CRI Average > 95
TLCI Average > 94

LIGHT ENGINE

850 W MSL ENGINE
(Multi-Spektral LED Engine)

PAN/TILT

PAN: 540°
TILT: 270°

LIGHT APERTURE

5m at 5600K, Min. Zoom: 46300 lux
5m at 3200K, Min. Zoom: 35000 lux

POWER

Voltage Input Range:
100-240 V

Power Consumption:
1150 W max.

DIMMING

Continuously 0 - 100%

L3™ - Low Light Linearity:
18 bit dimming for ultra
smooth fade to black

ROBE T2 PROFILE



SPECIALS

Moving Head
DataSwatch™ Filter: 237 Colors and Tones
Tungsten lamp effect
Color Picker Tool
Variable internal Frost 1°- 5°
Variable Focus, Iris, Shutter (Default 32)
Zoom Range 5°-55°
Effect Modes:
Rotating gobo wheel, Static gobo wheel, Animation Wheel,
Framing Shutters, 6-facet circular and linear prisms
Pan and Tilt transport locks (release before turn on!)
For Studio use only

MOUNT

0°, 32°, 90° / Universal operating position
Mounting points: 5 pairs of 1/4-turn locking points
2x Omega adaptors with 1/4-turn quick locks

CONTROL OPTIONS

On-Board Control on Graphical Display
Wireless DMX
W-DMX
REAP - Robe Ethernet Access Portal
RDM, ArtNet, MA Net, MA Net2, sACN

CONNECTIVITY

Power connector: powerCON
DMX and RDM data in/out:
Locking 3-pin & 5-pin XLR
Ethernet port in/out: RJ45